



Dimensions	86L X 86W X 38H
Standard Structure	Stainless steel Panel, Steel Button
Current Rating	3A,36VDC Max
Output Contact	NC\COM
Mechanical Life	1000000 tested
Suitable for Door	Hollow Door
Operating temp	-10℃ ~ 55℃ (14°F-131°F)
Operating Humidity	0-95% (non- condensing)
Weight	0.15kg
Standard Packing	70pcs





1. 2. 3. 4. 5. 6. 7. 8.

- 1, 2, 3, 4, 5, 6, 7, 8
- 2, 3, 4, 5, 6, 7, 8
- 3, 4, 5, 6, 7, 8
- 4, 5, 6, 7, 8
- 5, 6, 7, 8
- 6, 7, 8
- 7, 8
- 8



金橋 GOLDBRIDGE 有限公司 CO., LTD

地址:

Building 405, Shangbu Industrial
Area, Futian District, 深圳市福田区, 518031

电话 : + 0086-755-83767678 手机 : +
0086-755-88391348

联系人 : Lily Jiang

微信 / whatsapp / wechat : +
0086-13554918707

电子邮箱 : lily-jiang1206

电子邮箱 : sales (at) goldbridge sz.com

公司网站 : [http : // www. goldbridge
sz.com](http://www.goldbridge.sz.com)