



ACM-A60 00 00 0000 0000 0000, 00 00 00 0, 00
0 0000 00 00 0 0000 00 00 **Wiegand** 00 0 000
00 0000 0000 0 0000. 00 000 000, 00 0 000 000
00



1. 本報告係根據本會所屬之「國家安全情報中心」所蒐集之資料，經本會整理、分析、彙編而成，其內容係屬國家安全情報，除依法保護外，並應遵守下列事項：

2. Wiegand 26 00 0 000 0000 00 0000 000 0 0000.

3. 00 00, 0000, 0000 3 00 00 00 00.

4.reader, 0.1

5. 一个三位数除以 8000 的商是 10。

□□ □□□ □ □□□ □□□ □□□ 6.high □ □□□□□ □□,
□□.

7. .

11

ACM-A60 100 RFID 100 100 100 100 LED 100000 100 8000 100 100

Touch metal door access controller

Support rfid card, password,
rfid card + password.
Support 8000 user capacity

Support fast data copy



Lightning delivery



Global sales



Package mail



Technical support



After-sale

Product function

- ◆ Touch control waterproof panel,
- ◆ Metal casing with blue backlight
- ◆ WG26 / 34 input / output
- ◆ Support card, pin, card + Pin
- ◆ Full programming from the keyboard
- ◆ Human tampering alarm function
- ◆ Can set the management card
- ◆ Active and passive lock signal output
- ◆ Imported double point relay output signal
- ◆ Non contact type for radio frequency identification transponder technology
- ◆ Connect to the external release button (exit button)
- ◆ Memory capacity: 8000 user cards and 1 passwords
- ◆ Do not need to be connected to the computer, it can work alone
- ◆ The same series of access control supports data backup and backup
- ◆ Can be used to read the header and a machine



00-000

Wiegand 26 00 00, 00 00 00 0000 0000 00 00

产品解析

Product analysis



Work indicator



Touch waterproof
button & Card area



Door bell



00 00000 000

000 0000 000 00 000000 000 00 0000 00 0000 00 0000 000 0000.



ACM223

RFID 卡片 125Khz 125/4000 US 125Khz, EM 卡片

ACM209-NW

RFID (125Khz) 卡片, 125Khz EM 卡片, 125/4000 US 125Khz

ACM208

RFID 卡片 125Khz 125/4000 US 125Khz



ACM210

RFID 125Khz EM, Wiegand 26bit

ACM225

RFID 125Khz EM, Wiegand 26bit

ACM211B

RFID 125Khz EM, Wiegand 26bit

