



□□ □□□□ □□□□ □□□□ □□ □□ □□ **RFID** □□ □□ □□ □□ □□□□  
 □□□□ □□ □□ □□ □□ □□ □□ IP68 □□ □□□□ RFID 125 □□ □□□□ □  
 □□ □□□□ □□ □□ □□ □□ Wiegand□ □□ 2000 □□□□□ □□ □ 26

□□□□	ARM926EJ-S □□□□, 32 □□ RISC □□ □□ □□□ : 250MHz
□□□□□	2.4 □□ TFT □□□□ □□ □□□
□□ □□□	5,000
□□ / □□ / <b>PIN</b> □□	5,000
□□ □□	100,000
□□	□□, □□□□, □□□□ □ (□□□□ □□)
□□	TCP / IP; USB □ □□□□; WIFI □ RS485 □□
□□ □□	RFID □□ □□ (125KHz); MIFARE □□ (13.56MHz) □ □□
□	□□ □□□ □ (□□□□□ □); □□ □ □□
□□ □ (26/34)	1 Wiegand □□; 1 Wiegand □□
<b>TTL</b> □□	□□ □□ □□; □□ □□ □□; □□ □□ □□
□□□□ □□	□□□□ □□ □□; □□ □□ □□
□□□□	□□ □
□□	□□ □□; □□ □□□□ □□ □□□□□□. □□ □□ □□; □□ □□
□□	DC 12V / 1A
□□ □□	□□ □□ : 0 °C ~ 45 °C
□□ □□	□□ : 20 % ~ 80 %
□□	200 (L) * 96 (W) * 30 (H) mm



□□□□ □□

ACM9800□ □□□□□□ □□ □□□ □□□□. □□ □□□, □□ □□□, □□□ □□□ □□ □□ □□ RFID □□ □□□□ □□ □□□ □ □□□□.

□□

1. □□□, □□ □□ □□.
2. WAN □ LAN□□ □□□□ □□□□□□ □□□ □ □□□□
3. Cloud Sever □□□□□□ Websocket API □□ (2 □ □□□□□ □□ SDK)

□□ □□

□□□ hote □ □□□ □□ □□ □□□ □□ RFID □□□ □□ □□ □□□□ □ □ ACM9800 □□ □□





## ACM208

RFID 125KHz EM, Wiegand 26bit



## ACM210

RFID 125KHz EM, Wiegand 26bit

## ACM225

RFID 125KHz EM, Wiegand 26bit

