Product description

4-port network access controller with wide voltage power supply controller with metal housing

Here are the specifications of the network IP controller details:

| There are the specifications of | | | |
|--|--|--|--|
| Parameter | Single door control panel | Multi Door Control Panel (2) | Multi Door Control Panel (4) |
| ACM model | ACM-001 | ACM-002 | ACM-004 |
| Communication | Adaptive TCP / IP 10M / 100M | Adaptive TCP / IP 10M / 100M | Adaptive TCP / IP 10M / 100M |
| Description | Control 1 door, enter and exit the door by sliding the card or enter by sliding the card and exit the door via the button | Control 2 doors, enter and exit the door by sliding the card or enter by sliding the card and exit the door via the button | Check 4 doors, enter door by sliding card and exit door by button |
| PCB board size | 160mm * 106mm | 160mm * 106mm | 218mm * 106mm |
| Case size | 273mm * 228mm * 65mm | | |
| Power supply | 12VDC 4-7A | | |
| Energy consumption of the circuit | Less than 100 mA | | |
| Player input format | Wiegand 26 (All protocol compatible card readers, such as Motorola ,HID, EM, Mifare one etc.) | | |
| Quantity of readers | 2 pcs | 4 pcs | 4 pcs |
| Door controlled | 1 door | 2 doors | 4 doors |
| Door opening time extension setting | 1-600 seconds (adjustable) | | |
| Maximum amount of controllers | Without limits | | |
| Operating temperature | -40 °C ~ 70 °C | | |
| Operating humidity | 10-90% relative humidity, non-condensing | | |
| Q 'ty of users | 20,000 users | | |
| Amount of event buffers (offline) | 100,000 event buffers | | |
| Power failure protection measure | High speed memory, records never lose | | |
| Maximum distance from reader to controller | 100m (suggested distance 80m) | | |

| Maximum distance between controllers | TCP / IP: De | pends on the net cov | erage area |
|---|--|----------------------|------------|
| Package Included: | PCB board, software, manual, certificate. cardboard | | |
| Long time open door alarm, illegal break-in, intimidation | Yup | | |
| Fire and alarm connection | If no connection with the expansion board, it only has the software interface alarm and drive the computer speaker. If connected with expansion card, it is capable of alarming via hardware, if connected with hardened expansion card, then it is capable of security alarm, the model is ACB-EA05 | | |
| Door open and closed complsive for a long time | Yup | | |
| Remote open door | Yup | | |
| Interlock | No | Yup | Yup |
| Anti pass back and tail | Yup | Yup | Yup |
| Multi-card open door | Yup | | |
| Open for a long time at the specified time | Yup | | |
| Electronic map | Yup | | |
| Urgency block | Yup | | |
| First release of the card | Yup | | |
| Unlock based on internal and external validation | Yup | | |
| Keyboard (card + passwor, dinner password) | Yup | | |





ACM-T04 > Four-door TCP/IP Network Door Controller

- 1. Control 4 doors, 4 readers.
- 2. Communication Protocol: TCP/IP;
- 3. Door control: 1 door, 1pc relay;
- 4. Power Supply Input: 12V DC;
- 5. High Speed Memory, Records never lose







Wide voltage backup power controller listed here

Input: AC110-240V / 50Hz-60Hz, Output: DC9V-16V / 5A

Support FREE OEM silk screen printing LOGO IF based on 100pcs OTY

| Support TREE OLM SIIK Screen printing LOGO II based on 100pcs Q11 | | | |
|---|--|--|--|
| Product parameter | Parameter description | | |
| ACM model | ACM-WG04 | | |
| product name | Backup power supply for access control card | | |
| | | | |
| Input voltage | AC110-240V / 50Hz-60Hz | | |
| Output voltage | DC9V-16V / 5A | | |
| Output contact | Lock, access control, exit button | | |
| Material | Shell: iron material, painted | | |
| Time relay | 0 ~ 15 sec | | |
| Useful to | ACM series access control card. | | |
| Special design | box can accommodate backup power and control board | | |
| optional accessories | ACM-400 battery, 12V / 7AH | | |

| Dimensions | 371 x 266 x 66 mm (mm) |
|------------------|------------------------|
| | |
| Unit of weight | 2.04KG |
| Standard package | 10 PIECES |
| Carton weight | 20.5 kg |
| Carton size | 58 * 43 * 40 (cm) |



Application

Scope of Application



Packaging and delivery

Every order we will check the quality first to ensure our customer get the best product. Our staff will carefully pack it to avoid damage in transit. We will ship all goods as soon as possible.







Shipping method (for new customers reference only)

We have been one of the leading exporters of RFID products in China for 2000 years. With rich experience in international trade, we know international shipping very well, we know which express or air / sea line is cheap and safe for your country. We can provide various certificates to clean your custom such as CO, FTA, Form F, Form E ... We will provide our professional suggestion for shipping. EXW, FOB, FCT, CIF, CFR ... trade terms are ok for us. We can be your reliable partner for products and shipments.

We are professional suppliers of full security access control products with 20 years of experience, we make sure to offer the best access control system solution! Then, submit your inquiry details below, click "Send" now!

We are looking forward to establishing successful business relationships with new customers around the world in the future.

You May Like





ACM-K2A / B

No touch Door Realese Exit Button with led

ACM-Y180

Magnetic Surface Mount Lock (180kg)

ACM-Y806-5A

5A power supply for access control





ACM225

Touch Keypad RFID Access Control 12khz

ACM-210

Metal Waterproof RFID Wiegand Access Control

ACM26X

125Khz EM Card RFID Reader Dimensions: $115\text{mm} \times 75.5\text{mm} \times 16.8\text{mm}$

Our service

- 1, All inquiries will be answered within 24 hours
- 2, professional manufacturer and supplier, welcome to visit our website and factory
- 3, OEM / ODM available
- 4, high quality, fashin design, reasonable and competitive price, fast delivery time
- 5, after-sales service:
- 1), All products will have been strictly checked in house before packing
- 2), All products will be well packed before shipping
- 3), All of our products have 2-3 years warranty if the damage is not caused by man
- 6, faster delivery : About $1 \sim 5$ days for sample order, $7 \sim 30$ days for bulk order
- 7, payment: You can pay for the order via: T / T, Western Union, Paypal,
- 8, Shipping: We have strong cooperation with DHL, FEDEX, TNT, UPS, EMS, Forwarder by SEA and By AIR, you can also choose your own forwarder.

FAQ

Q: 1. How can I place an order?

A: Please list your needs by mail. Then we will send you the offer as soon as possible, after your

order is confirmed, we will arrange the production as soon as possible.

Q: 2. What about payment and shipping?

A: Trade assurance and T / T, Paypal, Western Union.

Customers can choose by sea, air or express (DHL, FedEx, TNT UPS etc.)

Q: 3. How can I get a sample to check the quality?

A: We could provide you with free sample and the freight cost paid by you.

Q: 4. How long can I expect to get the samples?

A: It depends on the quantity. Normally 3-7 days for 5000 pieces and 7-15 days for 100,000 pieces

Q: 5. Can your products be customized?

A: Almost all of your products are customized, including matter, size, thickness and printing. OEM orders are welcome.

Q: 6. Are you a trading company or a factory?

We are one of the largest manufacturers of RFID card / NFC tag / RFID keybod / RFID bracelet, rfid reader and access control products in China for more than 20 years.