

# MIFARE

215 (504 bytes), NTAG ACM-ABS006 DESFire

S  
W  
K  
H  
M  
P  
R  
S  
D  
B  
R  
L  
S  
B  
E  
D  
E  
FAQ

## RFID-чип

Customized size

ICCODE

ICCODE? 1) NTCG? Seal? 4K

Standard size CR80

?? ?? ?? ?? 4K? EV1 2K/4K

ISO 15693/ISO 18000-3 protocol:

?? DESFire?

MIFARE? DESFire? ?

MIFARE? DESFire? ?

MIFARE? DESFire? ?

Original wood color

?

1) HTKG? NTAG? ?? ?? ?? ?? ?

NTAG? X 2K / X 4K, MIFARE Plus

DESFire? RFID chip? ?? ?

related products

Color:

ICCODE? ?? SLIX-L, ICCODE? ?

ICCODE? S 2K / S 4K, MIFARE Plus



ACM-ABS004  
212 (128 bytes)  
ACM-ABS008  
4K / EV1 4K / EV2 4K



C(148 bytes)







?





## DESFire

Environment protection  
Glossy surface



**ACM-ABS003**

4: NFC forum type 2:

**ACM-ABS008**

1: MIFARE Classic

**ACM-ABS004**

203 (144 bytes), NTCG







### **ACM-ABS001**

S 1K SE, MIFARE Plus

### **ACM-ABS006**

3, OEM/ODM available

ACM-KEYFOB036

Hotel Key Rfid Wood Card

?

#### Application

ISO/IEC 14443A protocol:

MIFARE

MIFARE Classic 1K

Size:

Type of product:

8, shipping:

2) MIFARE Ultralight

RFID type: 210 (48 bytes), NTAG

? 2K / EV1 2K / EV2 2K

? 1K, classic MIFARE

SLIX 2

## **7, Payment:**

EV1 1K, classic MIFARE

## **Material:**

3: MIFARE

2: MIFARE Plus

## **Peculiarity**

Product Description

## **8K / EV1 8K / EV2 8K**

SLIX, ICODE? SLIX-S, ICODE

## **Our service**

(48 bytes) MIFARE Ultralight

## **A light weight**

6, faster delivery