Descrição do Produto

Descrição do Produto

Características:
1. Leitura e escrita na área limitada do equipamento acima de 0-60 CM do espaço estreito;
2. Fornece SDK de configurações e pode fornecer rotinas de desenvolvimento C #, VC, VB, Java;
3. A área EPC, as reservas, a função de desbloqueio de suporte da área do usuário, podem ser usadas para requisitos de privacidade e segurança de ocasiões especiais;
4. Apoie a função discriminante adjacente, pode evitar com um cartão em curto espaço de tempo (1-255 segundos ajustáveis) upload de repetição dentro;
5. Suporta operação de gravação rápida, conveniente para leitura e gravação.
Descrição do Produto:

Especificações	
Freqüência de Trabalho	902 ~ 928 MHz ou 865 ~ 868 MHz
Protocolo	ISO18000-6C (EPC C1 GEN2)
Porta de comunicação	USB esquerdo para porta serial / USB direito para saída de dados
Software e SDK	DEMO e C #, VC, VB, Java, DELPH, etc.,
Encriptação	Pode ser criptografado diretamente, prevenção de cópia.
Alcance de leitura	Leitura estável 0 ~ 60cm
Alcance de escrita	Escrita estável 0 ~ 10cm
Parâmetros físicos	
Adaptador	USB
Potência de saída	0 ~ 17dBm
Temperatura de trabalho	-20 ℃ ~ + 55 ℃
Temperatura de armazenamento	-20℃~ + 55℃
Tamanho do item	142x 85x20mm
Tamanho do pacote	180x120x50mm
Peso líquido	500g
Material de casca	abdômen

Mostra de produtos:

UHF
SPEEDWORK

Back Design in Black

Interface de software:


UHF Discrecte devices Reader/Writer V1.12
General
Tag access
Communication parameters
Parameters setup
USB Output Format(only double usb device)
Tag counts: 0
counts: 0
Communication mode
SerialPort
TCP/IP
PortNo
COM5
COM5
Baud Rate
9600bps
Device No.
0
Update
Connect
Disconnect
Work mode
Active mode
Timing mode
No.
Data
Counts
Ant
DevNo
Ascending
Descending
Save as file
Read
Start
Stop
Clear
192.168.8.200
Port
4196
Reader Version:6.99


R2kDemo V1.3
General
Tag access
Communication Parameters
Tag counts: 0
Counts: 0
Communication mode
SerialPo
TCP/IP
10.10.100.254
Update
Port
20058
Connect
Disconnect
Reset
Antenna parameters
Work time(ms)
Power(dbm)
1
2000
30
2
2000
30
3
2000
30
4
2000
30
Read
Set
No.
Data
Counts
AntNo
DeviceNo
Ascending
Descending
Auto save as file
Inv Once
Start
Stop
Clear
UHF Discrecte devices Reader/Writer V1.12
Tag counts: 11
counts: 100
1 30 33 30 35 10 03 02 67 10 70 DA 68 5 0 0
2 E2 00 30 32 81 17 02 80 12 34 56 78 6 0 0
3 FF FF FF FF FF FF FF FF FF FF FF FF 5 0 0
4 E2 00 30 74 19 13 00 15 17 90 5C 44 13 0 0
5 E3 00 11 22 18 19 12 34 12 34 77 88 13 0 0
6 E3 00 33 44 33 44 55 66 77 88 99 AA 2 0 0
7 47 43 31 35 30 36 30 30 30 30 30 6A 1 0 0
8 30 08 33 B2 30 09 01 40 00 00 00 00 24 0 0
9 E2 00 30 98 97 09 01 24 09 70 B7 A7 9 0 0
10 E2 00 30 98 17 13 02 34 21 10 30 BC 9 0 0
11 E2 00 30 32 74 08 00 32 12 10 88 99 13 0 0
Reader Version:5.34
Read
Start
Stop
Clear


UHF Discrecte devices Reader/Writer V1.12
Fast writing mode
Fast Write
Auto increment 1
Clear
Reading/Writing specific zone
Bank
EPC
Start address
2
Length
6
Read
Write
Clear
E3 00 11 22 18 19 12 34 12 34 77 88
Advanced operating
Access password
Operating zone
Lock tag
Unlock tag
Kill Password
Kill tag
Initialize tag
Working mode
Work mode
Timing mode
Active mode
Trigger mode
Timing interval
20
*10ms
Read
Default
Set
Communication mode
Com Link
RS232
Baud rate
9600bps
Reader parameters
DeviceNo(0-255)
0
Power(0-150)
150
Read mode
EPC single tag
frequency
Frequency hopping
Clear

Inscrição:
Tráfego inteligente como ETC;
Passagem de fronteira alfandegária, estacionamento, ponderação automática;
Logística como gerenciamento de contêineres, gerenciamento de paletes, gerenciamento de ativos etc;
Bilhetagem e controle de acesso;
Produtos farmacêuticos, como gerenciamento de resíduos médicos, etc.

produtos relacionados

Shenzhen Goldbridge concentra-se na inovação, R&D, produção e vendas de produtos IOT RFID e solução de aplicação, Categoria de leitor de rfid incluindo UHF desktop reader writer, UHF integrado reader, UHF R2000 fixo, UHF OEM module, RFID handheld reader, uhf rfid tags, active 2.4G rfid reader, EM 125KHZ Long range reader, hardware RFID industrial e software integrado, obteve a certificação empresarial nacional de alta tecnologia FCC, CE e ROHS.?

Raleted Long distance range RFID Reader & Tags

ACM-812A -8dBi 2-6 meter , 235x235x57mm	ACM-803A -9dbi 6-10 meters,260X260X45mm	ACM-811A-8dBi Muti-tag Reader, 6-9 meters, 255x255x45MM
ACM217-UHF UHF Reader and Writer - Provide Free program and SDK	ACM919L 4 Ports UHF Reader Impinj R2000 ,270mm*180mm*27mm	ACM-819A-12dBi Muti-tag Reader, 10-20 meters, 460x460x55MM
ACM8017 UHF Handheld Reader UHF +WIFI+GRPS Quad Band+Barcode 1D/2D	ACM09G-TCP/IP Or Wiegand Active 2.4G Reader 30-70meter, Provide FREE SDK and Demo	ACM08Y RFID EM 125Khz 70cm-1meter Middle long range Reader
ACM-MU85M One Antenna Port Module- 30dbm adjustable 0-15m used for handheld reader. ,55.5x39.5x7.6mm	ACM-MU82M 4 Antennas Ports Module 4ports 25m speed anti-collision impinj R2000 67.5mmx51mmx7.9mm	ACM-MU13M One Port Module Korea certificate 0-15m Size: 8x25x3.5mm
UHF Anti-metal Tag, ACM-UHF-M3: 135x22x12mm ±2mm	Anti-tamper windshield sticker tag (ACM-S001)	UHF ISO PVC Card Tag , 86x54mm (ACM-UHF Card)

Email: sales@goldbridgesz.com Web: http://www.goldbridgesz.com

About Us

Similar Products

GOLDBRIDGE

SHENZHEN GOLDBRIDGE INDUSTRIAL CO.,LTD

ACM Shenzhen Goldbridge
industrial company

As a one of leading exporter and manufactuer of RFID products in China , . We have been in this field for 17 years already . We have rich production and exportation experience on RFID products . Our strength products are : RFID card , RFID keyfob , RFID wristband , RFID tag and various RFID reader . We are also the access control solution provider .

FACTORY PHOTOS

Our Certificate

>>